

# PEPIO F6



**Present for R&D** by operability and user friendly set up design



Achieve to **high accuracy printing** by high precision design



**Possible to customize** for inline

## Basic Specifications

PEPIO F6			
Max.Work Size	(TD)160×(MD)160 mm	Machine Dimensions	(W)1859×(D)1404×(H)2047 mm
Substrate Thickness	0.05~2.0 mm	Machine Weight	Approx. 1600 kg
Max.Frame Size	(TD)200×(MD)260 t=5 mm	Power Supply	3Phase 200V 50/60Hz 6.9kW
Printing(off/set process)direction	Right → Left (Looking from Operation Side)	Air Supply	30ℓ/min 0.5MPa
Work Table	With Alignment Function		
Work Fixing Method	Adsorption by Vacuum Pump		
Vacuum Area	(TD)150×(MD)150 mm		
Vacuum Hole Diameter/Pitch	Φ0.8 mm /10 mm Pitch		
Off Set Speed	2~200 mm /s (Parameter Setting)		
Alignment Adjustment Camera	CCD Camera 2 units		
Camera view range	Approx. 6×6 mm		
Work Distance	Approx.170 mm		
Plate Table Fixing Method	Adsorption by Vacuum Pump		
Vacuum Area	(TD)190×(MD)250 mm		
Vacuum Hole Diameter/Pitch	Φ2.0 mm /10 mm Pitch		
Off Set Speed	2~200 mm /s (Parameter Setting)		
Table Speed during Coat / Print	2~200 mm /s (Parameter Setting)		
Blanket Cylinder Ref. diameter	Φ190 mm		
Blanket treatment	2.0~3.0 mm (Including Under Blanket)		
Printing Pressure (Cylinder pos. setting)	0~250μm (Parameter Setting)		
Rotation Speed Ratio (to work / plate)	-0.20~+0.20% (Parameter Setting)		

## Option Specifications

Auto 0 Point Setting	: Automatic
Anti static bar	: Blanket Cylinder near rear side of Printing
Dryer unit for balnket	: IR
Ink dispenser	: Ink dispenser (Pumping)
Blanket cleaner	
Full Frame Cover	: Without HEPA Filter



Specification to subject be changed without notice.